



Technical data

Voltage	U	230	V
Phase		1	~
Frequency		50	Hz
Speed		1360	RPM
Power consumption	P _e	420	W
Nominal current	I	1.9	A
Maximum current	I	2.1	A
Capacitor		12/400	µF
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class Fan		IP55	
Weight		18.2	kg
Packing dimensions		720x720x400	mm

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No
Intelligent Fan Drive	Yes

Characteristics

0 Pa	9050 m ³ /h
50 Pa	7700 m ³ /h




Please note: Picture may deviate from original product

Approval(s)




Wiring diagram - Fan

AA01 - 1 Phase - Standard - CCW



Dimensions



A01:	518 mm
A02:	620 mm
A03:	620 mm
A10:	7 mm
A11:	420 mm
A12:	33 mm
A13:	236 mm
A14:	365 mm
A15:	369 mm



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com